



BURGCAM-SMART-3020

WLAN 3MP IR camera for indoor use 2,3mm fix lens with audio-function, 5VDC

PRODUCT DESCRIPTION

> Application:

The WLAN cameras of the BURGcam series are small, unobtrusive and easy to operate. Hence they are ideal for use in private homes. The cameras can also be setup without a PC, e.g. by using a matching App. In case of a detected event, the camera will send a push notification to your smartphone/tablet. Video data can be exported to a micro SD card. The attractive design, the integrated IR LED and the duplex audio function complete this package.

► Technical specifications:

Туре	WLAN Camera on rotatable mount
Sensor type	1/3" Progressive Scan CMOS
Max. Picture resolution (pixel)	3 MP (2304(H)x1296(V))
Video codec	H.264, H.264B, H.264H, MJPEG
Max. frame rate (fps)	20 at 3 MP, 25 at 2 MP
Number of video streams	2 (1x Main, 1x Sub)
Lens mount	Intern
Iris control	DC
Lens type	Fix lens
Focal length	2,3 mm / F2.0
Angle of view (horizontal)	120°
Angle of view (vertical)	69°
Sensitivity (Lux)	0,9Lux/F2.0(color), 0Lux/F2.0 (IR on)
IR cut filter	ICR-IR-Cut filter
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	AGC, manual

SANTEC BW AG

An der Strusbek 31, 22926 Ahrensburg, Germany Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10 santec_info@burg.biz, www.santec-video.com



Technical specifications:

Digital noise reduction (DNR) 3DNR S/N ratio (dB) < 50 dB

White balance Auto / sunny / night / outdoor / manual

Backlight compensation BLC, HLC, DWDR

Wide dynamic range (WDR) DWDR

Digital zoom 16x, adjustable

Mirroring (vertical) Yes
Motion detection Yes

Privacy zones Yes, 4 zones

Region of Interest (ROI)

Tampering Alarm

Yes

Camera title

Tripwire (IVA)

Intrusion (IVA)

Scene change (tampering)

IVS Missing / Added

No

IVS Missing / Added No Video output No Audio detect (IVA) Yes

Audio support Yes, built-in microphone and speaker

Audio in-/outputs No

Audio codec G.711a / G.711Mu / AAC

Alarm contacts I/O 0 / 0

Alarm management HTTP, FTP, SMTP, ONVIF, NAS

Schedule Yes

Management software support Many VMS

Security features HTTPS, SSH

Max number of users 10

Supported protocols HTTP,TCP,UDP, DHCP,SMTP,UPnP,NTP, IPv4, IPv6, RTSP

Supported software standards ONVIF, PSIA, CGI

Internal memory Micro SD (optional), max. 128 GB

Video Content Analytics (VCA) No Ethernet connector WLAN

WLAN Wi-Fi (IEEE802.11b/g/n)

Supported browsers MS Internet Explorer version 11

P2P support Yes

Cloud service Yes, BURG-WÄCHTER cloud

Smartphone App BurgCam App

Storage SD-Card, NAS (SMB, NFS), PC local

Max. range (clear view) 50 m
Classification No
Vandal-proof No
Heater No

Installation Magnetic fixing and Desktop

Camera mounting Magnetic

SANTEC BW AG

An der Strusbek 31, 22926 Ahrensburg, Germany Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10 santec_info@burg.biz, www.santec-video.com



WLAN CAMERAS BURGCAM-SMART-3020

► Technical specifications:

Housing colour	White
Housing material	Plastic
Integrated IR-LEDs	Yes
Wavelength IR-LED	850 nm
IR distance (m. ca.)	max. 10
Voltage	5 V DC
Max. Power consumption (watt)	< 4,7 IR on
Operating temperature (°C)	-10 to +45
Rel. humidity (%)	Max. 95, non-condensing
Dimensions WxDxH (mm)	55,7 x 64,4 x 107
Weight	0,135 kg
Identifier	CE, RoHS
Items included in delivery	CD, software, quick user guide, power supply
Specials	WLAN, WPS, P2P, Cloud capable
Installation	Via WLAN (WPS) + App (Smartphone or Tablet)

Note:

A micro USB power cord is included in the delivery. A micro SD-card, however, is not included.

► Recommended Accessories

BURGCAM-REC-3510 Network rekcorder for 3,5" HDD

