



**THE PHOENIX VENUS HS0650 & NEPTUNE HS1050 SERIES** are designed to provide extreme security protection for domestic and business use.

- **SECURITY PROTECTION** – Tested to the prestigious European EN1143-1 Security standard. ECB.S Certified Grade 0 & I. **VENUS** – (Grade 0) has a recommended Insurance rating of £6,000 cash or £60,000 valuables\*. **NEPTUNE** – (Grade I) has a recommended Insurance rating of £10,000 cash or £100,000 valuables\*.
- **APPROVALS** – UK Police approved (Secured by Design scheme) and the Association of Insurance Surveyors (AiS).
- **FIRE PROTECTION** – Tested to the European LFS 30P fire protection standard (EN15659 ECB.S Certified) giving 30 minutes fire protection for paper records. **HS0656 & HS1056** – Tested to the European LFS 60P fire protection standard (EN15659 ECB.S Certified) giving 60 minutes fire protection for paper records.
- **KEY LOCKING** – Fitted with high security double bitted VdS class I key lock.
- **ELECTRONIC LOCKING** – Fitted with high security VdS class II electronic lock with dual control, master code & time delay.
- **FIXING** – Ready prepared for floor fixing, with fixing bolts for concrete supplied.
- **CONSTRUCTION** – 3 way 24mm diameter locking bolts, double wall construction with specially formulated concrete infill, anti-drill plates and re-locker protection, provide a safe of great strength.
- **COLOUR** – Finished in a high quality scratch resistant Graphite Grey paint RAL7024.

✚ Suitable for storage of controlled drugs whose active ingredients exceed 500 grams.

MODEL NUMBER	EXTERNAL DIMENSIONS H x W x D	INTERNAL DIMENSIONS H x W x D	DOOR SWING / HANDLE DEPTH	WEIGHT	CAPACITY	SHELVES		
						LEVER ARCH FOLDER (H320xW75x290mm) Total no.of file per unit	FOOLSCAP LEVER ARCH FOLDER (H350xW80xD285mm) Total no.of file per unit	FOOLSCAP BOX FILE (H370xW75xD245mm) Total no.of file per unit
HS0651K/E HS1051K/E	340 x 500 x 345mm	262 x 424 x 216mm	475/40mm	104kg	24 Litres	1	0	0
HS0652K/E HS1052K/E	440 x 500 x 432mm	362 x 424 x 302mm	475/40mm	141kg	46 Litres	1	5	0
HS0653K/E HS1053K/E	900 x 440 x 430mm	822 x 364 x 300mm	415/40mm	230kg	90 Litres	2	8	8
HS0654K/E HS1054K/E	840 x 650 x 550mm	765 x 574 x 420mm	626/40mm	320kg	184 Litres	2	14	14
HS0655K/E HS1055K/E	1240 x 650 x 554mm	1163 x 574 x 424mm	626/40mm	452kg	283 Litres	2	21	21
HS0656K/E HS1056K/E	1950 x 940 x 585mm	1760 x 800 x 392mm	613/40mm	658kg	553 Litres	4	50	40

Door aperture is reduced by 20mm due to frame.



\* Ratings are approximate only and may vary due to area conditions and location. Please check with your underwriter.