Rim Locks - Double Security

4L67E

BS High Security Rim Lock



| Application: | Recommended by Insurance companies and the police For timber doors from 38-57mm thick, hinged on the left or right and opening inwards only Suitable for glass panelled doors only | | |
|----------------------|---|---------------------|----------------------------|
| Specification: | Automatic internal and external deadlocking Key operation from the outside. Key lockable knob operation from the inside Hardened steel 20mm deadbolt which automatically deadlocks on closing the door High security cylinder: Hardened steel plates and pins protect from drill attack Resists torque attack High level of protection against picking and manipulation Drill, saw and force resistant Backset: 60mm Cylinder: 10 disc Ava mechanism Keying: May be supplied to differ or to pass Key Blank Number: B-K734-M Keys supplied: 3 keys Available Boxed or Visi Packed Available in BLX and PB finishes A Door Pull, V-4LP-EB, is also available for use with this product - PL finish only | | |
| | | | Standards: • Kitemarked |
| Finish: | BLX - BrassluxPB - Polished Brass | | |
| Variants: | V-4L67E-B-PL | High Security AVA R | im Lock - Visi |
| | V-4LP-EB | Door Pull - Visi | |
| | | | |
| Technical Design: | | 53mm | 25mr |



d to BS3621



27mm

37mm

70mm

П 85mm