



BURGCAM-ZOOM-3060

WLAN 2MP PTZ dome camera for indoor and outdoor
2,7-11 mm autofocus lens, 12VDC, IP-66,IK10,IVA

PRODUCT DESCRIPTION

► Application:

The WLAN cameras of the BURGcam series are small, unobtrusive and easy to operate. Hence they are ideal for use in private homes. The cameras can also be setup without a PC, e.g. by using a matching App. In case of a detected event, the camera will send a push notification to your smartphone/tablet. Video data can be exported to a micro SD card.

► Technical specifications:

Type	WLAN PTZ camera
Sensor type	1/2.7" Progressive scan CMOS
Max. Picture resolution (pixel)	2 MP (1920x1080)
Video codec	H.264, MJPEG
Max. frame rate (fps)	25/30 fps at 1080P/720P
Number of video streams	3 (individually adjustable)
Lens mount	Intern
Iris control	DC
Lens type	4x autofocus lens
Focal length	2,7 - 11 mm / F1.6
Angle of view (horizontal)	112,5° - 30°
Sensitivity (Lux)	0,05Lux/F1.6(color), 0,005Lux/F1.6(b/w)
IR cut filter	ICR-IR-Cut filter
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	AGC, manual
Digital noise reduction (DNR)	Ultra 2DNR / 3DNR
Shutter (sec.)	1/1 - 1/30,000

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

S/N ratio (dB)	< 50 dB
White balance	AWB / manual
Backlight compensation	120 dB True WDR, BLC, HLC
Wide dynamic range (WDR)	120 dB WDR (True WDR)
Tilt angle (°)	0° to 90°
Rotation radius	355°
Preset positions	300
Rotation speed	0,1° bis 100°/s.
Tilt speed	0,1° to 60° /s
Preset speed	Pan: 100°/s, Tilt: 60°/s
Tours	8
Digital zoom	16x, adjustable
Mirroring (vertical)	Yes
Motion detection	Yes
Privacy zones	Yes, 24
Region of Interest (ROI)	Yes
Tampering Alarm	Yes
Camera title	Yes
Tripwire (IVA)	Yes
Intrusion (IVA)	Yes
Scene change (tampering)	Yes
IVS Missing / Added	Yes
Video output	No
Audio detect (IVA)	No
Audio support	No
Audio in-/outputs	No
Audio codec	-
Alarm contacts I/O	0 / 0
Alarm management	HTTP, FTP, SMTP, ONVIF,NAS
Schedule	Yes
Management software support	Many VMS
P2P support	Yes
Cloud service	Yes, BURG-WÄCHTER cloud
Smartphone App	BurgCam App
Access	Browser / Client SW / Mobile App
Storage	SD-Card, NAS (SMB, NFS), PC local
Security features	HTTPS, SSH
Max number of users	20
Supported protocols	HTTP,TCP,UDP, DHCP,SMTP,UPnP,NTP, IPv4, IPv6, RTSP
Supported software standards	ONVIF, PSIA, CGI
Supported browsers	MS Internet Explorer version 11
Internal memory	Micro SD (optional), max. 128 GB
Video Content Analytics (VCA)	Tripwire, Intrusion, Face detect, etc.
Ethernet connector	RJ-45, WLAN

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 santec_info@burg.biz, www.santec-video.com



► **Technical specifications:**

WLAN	Wi-Fi (IEEE802.11b/g/n)
Ethernet standards	10Base-TX/100Base-TX
Max. range (clear view)	50 m
Classification	IP-66, IK10
Vandal-proof	Yes, acc. to IK10
Heater	No
Installation	Wall and ceiling mount
Camera mounting	Screw mounting
Housing colour	White
Housing material	Aluminium
Integrated IR-LEDs	No
DORI max. (Detect-Observe-Recognize-Identify)	120m - 48m - 24m - 12m
Voltage	12 V DC
Max. Power consumption (watt)	10
Operating temperature (°C)	-30 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions ØxH (mm)	122,8 x 95,9
Weight	0,66 kg
Identifier	CE, RoHS
Items included in delivery	CD, software, quick user guide, power supply
Specials	WLAN, WPS, P2P, Cloud capable
Installation	Via WLAN (WPS) + App (Smartphone or Tablet), LAN

► **Note:**

A power adapter is included in the delivery. A micro SD-card, however, is not included.

► **Recommended Accessories**

SNCA-MK-4631	Adapter / mounting kit for SNC-211FDIA and SNC-231RZNA
SNCA-WM-4644	wall bracket for SNC-431FEIF, 211FDIA, SCC-241KDIA, SNC-231RZNA
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
BURGCAM-REC-3510	Network rekrcorder for 3,5" HDD